

CW

Carton wrapping machine



Features and benefits

- AC drives and motors – High reliability
- SIGNODE- Powered pre-stretch, Variable up to 300%
- Independent film tension adjustment for wrapping both light and heavy cartons
- PLC Controlled with digital display of stretch % and weight of the film consumed/ carton
- Convenient operating height
- Top holding attachment for holding the carton while wrapping

 **SIGNODE**[®]

Your partner in industrial packaging world wide

Carton wrapping machine

Technical specifications

MACHINE

Over all dimensions	:	910(W) x 1515(L) x 1630(H)
Machine weight	:	400kg (max.)

LOAD

Over all dimensions (max.)	:	750(L) x 500(W) x 500 (H)
Over all dimensions (min.)	:	200(L) x 200(W) x 200 (H)(with 10" film width)
Load diagonal	:	910
Weight	:	200 kgs. max.(Centred)

TURN TABLE

Dimensions	:	910 diameter with variable speed
Suspension	:	2 nos. Taper roller bearing
Motor	:	0.5 HP, 415 V, 3 Phase
Gear reducer	:	Worm reducer

Powered variable pre-stretch unit

Stretch	:	Variable up to 300%
Motor	:	0.5 HP, 415 V, 3 Phase

FILM

Size	:	500 Width x 250 Dia.(max.) x 76 Core Or 250 Width x 250 Dia.(max.) x 76 Core
Elongation	:	Up to 300 %

Note:

- 1) All Dimensions are in mm.
- 2) Carton needs to be turned by 90° for full wrapping.
- 3) Optional- Pneumatic up down of the sensor stretch unit to wrap more height of the carton.



HARI OM ENTERPRISES

H.O. : G-15, Geetanjali Tower, Madrampura,
Ajmer Road, Jaipur, Raj. 302019
Mob : 09414051490

B.O. : G-23, Neemrana Central, Neemrana,
Alwar, Raj. 301705
Mob : 09930792807

E : hariomenterprises@yahoo.co.in
info@hariomenterprises.org
sales@hariomenterprises.org

W : www.hariomenterprises.org