

# FTM

## Flexible taping machine



### Features and benefits

- Twin mast column for greater stability during operation
- Auto on/off- for power saving
- Digital carton counter
- Separate top and bottom drive for perfect and uniform taping
- Uniform and controlled pressure during taping
- Twin flap squeeze rollers provides additional squeezing for perfect top alignment
- Belt speed of 20 m/minute
- Inbuilt tool box- Ease of maintenance

**SIGNODE®**  
Your partner in industrial packaging world wide

## Flexible taping machine

### Technical specifications

#### Machine specification

	FTM
Taping Head	Standard (2"/2.5"/3"), Flexible ( 2"/2.5")
Length	1590 mm( With 0.5 Mtr Conveyor)
Width	810 mmHeight1400 mm
Weight	155 Kg
Color	RAL 6000 & RAL 1021 Yellow (Moving Parts)
Drive Motor	0.25 HP, 2 No.
Belt speed	20 Metres/ Min
Machine through put	Belt speed/( Carton length+280 mm)

#### Utility requirements

Air requirement	NA
Air consumption	NA
Power supply	415 V AC, 3 Phase, 50 Hz
Power consumption	0.36 KW
Tap Roll length	65 M / 650 M/ 1000 M

#### Case dimensions

Length	150 mm - Un Limited
Width	160 mm -550 mm
Height	100 mm -550 mm
Weight	2- 50 Kg
Carton Ply	Min 3 Ply

### User friendly

- Self-centering side guides for accurate centering
- Positive top and bottom drive to ensure sealing of tall and heavy cartons, in addition to regular cartons
- 500 mm extra conveyor at entry/ exit for ease of operation
- Telescopic legs for height adjustment

### Safety

- Conformance with CE norms
- Emergency Stop Pushbutton
- Belt guards for operator safety
- Optional MS(wire mesh) /Polycarbonate safety Guards for additional safety



**HARI OM ENTERPRISES**

E : hariomenterprises@yahoo.co.in  
info@hariomenterprises.org

W : www.hariomenterprises.org

H. O. : G-15 Geetanjali Tower, Madrampura,  
Ajmer Road, Jaipur. Raj. 302019  
Mob. : 09414051490

B. O. : G-23, Neemrana Central, Neemrana,  
Alwar, Raj. 301705  
Mob. : 09930792807