

6AM

Heavy duty case sealer for tall and heavy cartons



Features and benefits

- Ideal for batch production of tall and heavy cartons
- Twin mast column for greater stability during operation
- Separate top and bottom Drive for perfect taping
- 3" drive belts for maximum load carrying capacity
- Uniform and controlled pressure during taping.
- Twin flap squeeze rollers provides additional squeezing for perfect top flap alignment.
- Belt speed of 20 m/minute as per international norms
- Inbuilt tool box for ease of maintenance.
- Self-centering side guides for accurate centering
- Positive top and bottom drive to ensure sealing of tall and heavy cartons, in addition to regular cartons
- Telescopic legs for height adjustment
- Quick and simple adjustment for varying carton sizes.
- Optional MS/polycarbonate Safety Guards with/ without electrical interlock for operational safety.

6AM

Heavy duty case sealer for tall and heavy cartons

Technical data

Machine Specification

6AM

Taping Head Flexible	:	(2"/2.5"/3")
Length	:	1030 mm
Width	:	826 mm
Height	:	1650 mm
Weight	:	198 Kg
Color	:	RAL 6000 & RAL 1021 Yellow (Moving Parts)
Drive motor	:	0.25 HP, 3 No.
Belt speed	:	18 Metres/ Min
Machine through put	:	Belt speed/(Carton length+280 mm)

Utility requirements

Air requirement	:	NA
Air consumption	:	NA
Power supply	:	415 V AC, 3 Phase, 50 Hz
Power consumption	:	0.4 KW
Tap roll length	:	65 M / 650 M/ 1000 M

Case dimensions

Length	:	150 mm - Un Limited
Width	:	225 mm -750 mm
Height	:	120 mm -750 mm
Weight	:	2- 60 Kg
Carton Ply	:	Min 3 Ply



HARI OM ENTERPRISES

H.O. : G-15, Geetanjali Tower, Madrampura,
Ajmer Road, Jaipur, Raj. 302019
Mob : 09414051490

B.O. : G-23, Neemrana Central, Neemrana,
Alwar, Raj. 301705
Mob : 09930792807

E : hariomenterprises@yahoo.co.in
info@hariomenterprises.org
sales@hariomenterprises.org

W : www.hariomenterprises.org